

Bus-Cam Clarity S4 HD 720p Mobile DVR



Main Features

- | Supports 4 ch AHD +1 ch IPC (compatible with analog, AHD and IPC)
- | Supports Dual SD cards for recording, each max. 128GB
- | Compact design, easy to install and modular design for easy maintenance
- | Dual streams for local recording and wireless transmission
- | New CMS platform for live view and remote management

Specifications

Order Number		106143
	Input	4 channel AHD/analog + 1 channel IPC
	Output	1 channel
Video	Recording	PAL: 4*WD1 @30fps+1*IPC 720p@30fps 2*AHD 720p@25fps+1*IPC 720p@25fps NTSC: 4*WD1 @30fps+1*IPC 720p@30fps 2*AHD 720p@30fps+1*IPC 720p@30fps
Audio	Input	5 channels
	Output	1 channel
	Audio Signal Standard	Electrical level: 2 Vpp Input impedance: 4.7kΩ
	OS	Linux
System	Control Mode	Touch screen, mouse control, IR remote control, Wi-Fi remote control, Network
	Display Split	1/4/9 Image display
Display	OSD	GPS information, alarm, vehicle number, speed, date/time
Recording	Video/Audio Compression	Video: H.264 Audio: ADPCM, G.711A, G.711U
	Image Quality	1-8 levels adjustable (1 = highest quality)

	Recording Mode	Ignition/Manual/Schedule/Alarm (sensor, speed, acceleration, video loss, temperature) Mirror recording
	Pre-recording	0-30 minutes
	Post-recording	0-30 minutes
Playback	Playback Channel	1 channel by local playback
	Search Mode	Date/time, channel, event
Network	Ethernet	100Mbps Ethernet port, aviation connector (RJ45 port optional)
	WIFI	Supports 802.11b/g/n (optional)
	3G/4G	WCDMA / EVDO / TDD-LTE / FDD-LTE (optional)
Locating	GPS	GPS module (optional).
Storage	SD	Supports Dual SD cards, max. 128GB each
	USB	USB 2.0
Interface	RS232	RS232 x 1, Support extension to 4 (232 x 2, 485 x 2)
	Sensor	8 inputs, 2 outputs
LED	PWR	Blue
	NET	Green
	ERR	Orange
	USB	Green
	ALM	Red
	REC	Green
Power	Input	DC 8-36V
	Output	5V@2A
Physical	Dimension (L x W x H)	6.57" x 5.74" x 2.13"
	Weight	1.98 lbs
	Protection	IP54
	Operating Temperature	-40°F to +158°(With heater) or 14°F to +158°F
	Operating Relative Humidity	8% - 90%